



BROTHERS
PHARMAMACH (INDIA) PVT. LTD.

LABELSTIK 150



TECHNICAL SPECIFICATIONS

Label Height : 8 mm to 90/120 mm Standard*
 Label Length : 12 mm Minimum
 Label Roll Dia. : 300 mm
 Core Dia. : 75/76 mm
 Gap Between two Labels : appx. 3 mm
 Product Diameter : 15 mm to 90 mm*
 Electrical : 220 VAC Single Phase Power Supply (50/60 Hz)
 Power : 1.0 Hp, 1.2 Amp.
 Capacity : 0.75 Kw
 Speed : Up to 120 Labels per minute depending on Product and Label Size
 Conveyor height : 830-875 mm*
 Overall dimension : 1830 mm(L) X 800 mm(W) X 1300 mm (H)

Machine Direction of Movement : Left to Right from operator side

* Specification can be changed as per customers requirements

Automatic Sticker Labelling Machine

The Automatic Vertical Sticker Labelling Machine Model LABELSTIK-150, is suitable for labelling on Round Vials and smaller size of Bottles. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. It is capable of Labelling up to 120 units per minute depending on product diameter and label size. Machine suitable for Vials and Small Sizes of Bottles from Glass, Plastic, PET, HDPE, PP etc. with speed range of 40 to 120 products per minute.

The Sticker Labelling Machine LABELSTIK-150 has its own unique single point synchronised speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the machine. The System thus saves valuable time, avoiding machine-down time, and helps achieve higher production.

BUILT-IN UNIQUE FEATURES :

- Dual Type Operation Control with Push Button as well as Colour Touch Screen
- No Label Data Input/retrievals require for any Label Size
- No Change Parts for Product and Label size
- Single Pot On-line Speed Variation control
- Synchronized speed of Label Dispensing, Conveyor and Pressing Device
- Virtually Maintenance free machine
- PLC Control System
- Easy to change Label application height
- User Friendly Label Placing Adjustments
- Self Protected against Voltage Fluctuations
- Suitable for On-Line InkJet and Contact Coding System
- Suitable for Partial, Full Wrap Around and Overlap Labelling
- Built In A.C. Variable Frequency Drive System.
- Fully Stainless Steel finish Machine

OPTIONAL FEATURES :

- Label Roll Empty - Machine Stop System with Alarm
- Special Label Sensor for sensing Transparent Film Labels which does not have any sensing mark on it.
- Option of Contact Coder, Hot Foil Coder, HP Cartridge Coder and Inkjet Coder with various speed range available.
- Tower Light showing the machine status
- Low Compressed Air - Machine Stop for pneumatically operated coding system
- Turn Table and Packing Conveyor

This Model is available with Limited optional features only and does not have all features mentioned in UNIQUE FEATURES Page.

Other Available Models

LABELSTIK-120C.Twin	LABELSTIK-120C	LABELSTIK-120H	LABELSTIK-150B
LABELSTIK-250C.Twin	LABELSTIK-300HG	LABELSTIK-300LR	LABELSTIK-300
LABELSTIK-120R.Twin	LABELSTIK-120R	LABELSTIK-600	LABELSTIK-400
LABELSTIK-100F.Twin	LABELSTIK-250F.Twin	LABELSTIK-EXCEL	LABELTUBE-60

Email : sales@brothers.in
 Export : sales1@brothers.in

Phone : +91 79 40213213 / 25831346

www.brothersindia.com