



**BROTHERS**  
PHARMAMACH (INDIA) PVT. LTD.

# LABELSTIK 300LR



### UTILITY REQUIREMENT :

Filtered Compressed Air : 4 to 5 Bar Air Pressure  
Electrical : 220 VAC 1 Phase Power Supply (50/60 Hz)  
Power : 2.5 Hp, 10 Amp., Capacity : 3.5 Kw

For Built-in / Optional\* Items Refer UNIQUE FEATURES Page for more details.

Email : sales@brothers.in  
Export : sales1@brothers.in

## Automatic Linear Sticker Labelling with Rotary Star Wheel System

Automatic High Speed Vertical Linear Sticker Labelling Machine with Rotary Star Wheel System Model LABELSTIK-300LR, is one of the most user friendly Sticker Labelling suitable to use for small diameter round products such as Vials, Eye Drop bottles etc. with speed upto 300 per minute. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. The machine is suitable for Labelling on Glass Vials, HDPE Eye Drop Vials and other Round Objects. It is capable of Labelling up to 300 units per minute depending on product and label size with the help of required change parts.

LABELSTIK-300LR having Rotary Star Wheel System to help and use unstable small diameter round product at high speed and similarly machine having Infeed and Exit Linear Conveyor system to connect labelling machine with any packing line for online operation. Machine with unique single point synchronised speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the Machine. The System thus saves valuable time, avoiding machine-down time, and helps achieve higher production.

Machine available with Various Standard as well as Optional Features such as Colour Touch Screen PC, Toughened Glass Safety Cabinet in Complete Stainless Steel Structure, Stepper or Servo Motor for high speed operation, Missing Label Detection in Roll, Missing Label Detection on Product, Online Product ejection system. Machine also available with unique Variable Speed Drive Control Product infeed belt which helps to achieve optimum speed for each product.

### TECHNICAL SPECIFICATIONS

Label Height : 8 mm to 50/70/90 mm Standard\*  
Label Length : 12 mm Minimum  
Label Roll Dia. : 400 mm  
Core Dia. : 75/76 mm  
Gap Between two Labels : appx. 3 mm  
Product Diameter : 15mm to 50 mm\*  
Speed : Up to 300 Labels per minute,  
Labelling Machine speed also depending on Product and Label Size  
Product Feeding Belt height : 850 mm\*  
Overall dimension : 2440 mm(L) X 1400 mm(W) X 1100 mm (H)  
With T.G. Cabinet : 2440 mm(L) X 1400 mm(W) X 1900 mm (H)

\* Specification can be changed as per customers requirements

### Other Available Models

LABELSTIK-120C.Twin	LABELSTIK-120C	LABELSTIK-120H	LABELSTIK-150
LABELSTIK-250C.Twin	LABELSTIK-300HG	LABELSTIK-300	LABELSTIK-150B
LABELSTIK-120R.Twin	LABELSTIK-120R	LABELSTIK-600	LABELSTIK-400
LABELSTIK-100F.Twin	LABELSTIK-250F.Twin	LABELSTIK-EXCEL	LABELTUBE-60

Phone : +91 79 40213213 / 25831346

www.brothersindia.com